

View Online at <https://aerobasegroup.com/nsn/5306-01-384-1152>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.350 inches

Fastener Length:

Between 1.365 inches and 1.385 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.365 inches and 0.385 inches

Shoulder Diameter:

0.164 inches second shoulder

Shoulder Length:

0.380 inches third shoulder and 0.420 inches third shoulder

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Shoulder Shape:

Round third shoulder

Special Features:

Second shoulder fully threaded .164-32unc-2a

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0