## NSN 5306-01-384-2035

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-384-2035

view Offinite at https://aerobasegroup.com/nsn/3300-01-304-2003
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.589 inches
Fastener Length:
Between 1.099 inches and 1.129 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.035 inches and 0.055 inches
Hole Diameter:
Between 0.060 inches and 0.070 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Head Minor Diameter:
Between 0.360 inches and 0.375 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
13500 pounds per square inch
Hole Configuration Style:
Spline
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response or ams 5663 assn standard single material response
Surface Treatment:

Passivate

## NSN 5306-01-384-2035

Shear Bolt - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0