## NSN 5306-01-384-5339

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-384-5339

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.345 inches and 0.395 inches
Fastener Length:
Between 0.543 inches and 0.573 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Hole Diameter:
Between 0.045 inches and 0.056 inches
Locking Feature:
Patch threads or strip threads or pellet threads
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.178 inches and 0.198 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
3a
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Material:
Plastic polyamide locking feature
Material Specification:
Mil-f-18240 military specification single material response locking feature
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener

## NSN 5306-01-384-5339

Shear Bolt - Page 2 of 2

Mil-f-18240 spec.



Thread Series Designator:
Unjf
Specification Data:
80205-nas6304 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):