

View Online at <https://aerobasegroup.com/nsn/5306-01-386-2146>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 21.5 millimeters and 28.7 millimeters

**Fastener Length:**

Between 34.50 millimeters and 35.50 millimeters

**Head Style:**

Hexagon

**Head Height:**

Between 5.1 millimeters and 5.5 millimeters

**Width Between Flats:**

Between 12.7 millimeters and 13.0 millimeters

**Thread Diameter:**

8.0 millimeters

**Grip Length:**

Between 6.80 millimeters and 13.00 millimeters

**Features Provided:**

Finished head

**Min. Tensile Strength (psi):**

1040 megapascals

**Hardness Rating:**

33.0 rockwell c and 39.0 rockwell c

**Minimum Yield Strength:**

940 megapascals

**Thread Pitch In Millimeters:**

1.25

**External Thread Tolerance Class:**

6g

**Material:**

Steel property class 10.9

**Material Specification:**

Ansi b18.2.3.1m, property cl 10.9 assn standard single material response

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Qq-z-325, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0