## NSN 5306-01-388-4446

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-388-4446

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.735 inches
Fastener Length:
Between 1.220 inches and 1.250 inches
Head Style:
Dished hexagon
Head Height:
Between 0.250 inches and 0.265 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.4990 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-388-4446

Shear Bolt - Page 2 of 2



**Specification Data:** 

80205-nas6708 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0