

View Online at <https://aerobasegroup.com/nsn/5306-01-389-0244>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.725 inches and 0.865 inches

Fastener Length:

1.015 inches

Head Style:

Countersunk cylindrical convex

Head Major Diameter:

0.402 inches

Internal Drive Style:

Hexagon

End Application:

Pacer dawn

Thread Diameter:

0.250 inches

Width Across Flats:

0.141 inches

Thready Qty Per Inch (tpi):

28

Countersink Angle:

100.0 degrees

Special Features:

O" ring synthetic rubber per mil-r-6855, cl i, grade 60: 5306-010 bolts are intended for use with 5310-039 receptacle, 5365-010 ring and 5325 -014 grommet

Material:

Steel comp 631 spring

Material Specification:

Mil-s-5626 military specification 1st material response fastener or mil-s-6049 military specification 2nd material response fastener

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-416, type ii, cl 2 federal specification single treatment response fastener

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.