

View Online at <https://aerobasegroup.com/nsn/5306-01-389-0255>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.725 inches and 0.864 inches

**Fastener Length:**

1.295 inches

**Head Style:**

Countersunk cylindrical convex

**Head Major Diameter:**

0.402 inches

**Internal Drive Style:**

Hexagon

**End Application:**

Pacer dawn

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

0.141 inches

**Thready Qty Per Inch (tpi):**

28

**Countersink Angle:**

100.0 degrees

**Special Features:**

O" ring synthetic rubber per mil-r-6855, cl i, grade 60: 5306-010 bolts are intended for use with 5310-039 receptacle, 5365-010 ring and 5325 -014 grommet

**Material:**

Steel comp 631 spring

**Material Specification:**

Mil-s-5626 military specification 1st material response fastener or mil-s-6049 military specification 2nd material response fastener

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-416, type ii, cl 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.