NSN 5306-01-391-0326

Shear Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-01-391-0326 |
|--|
| Thread Class: |
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.323 inches |
| Fastener Length: |
| Between 1.183 inches and 1.213 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.110 inches and 0.125 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.865 inches and 0.885 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard 1st material response or ams 5737 assn standard 2nd material response |
| Surface Treatment: |
| Aluminum |
| Thread Series Designator: |
| Unf |
| Specification Data: |
| 80205-nas6303 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5306-01-391-0326

Shear Bolt - Page 2 of 2

Fiig: A003b0

