

View Online at <https://aerobasegroup.com/nsn/5306-01-391-1563>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.902 inches

Fastener Length:

Between 7.137 inches and 7.167 inches

Head Style:

Dished hexagon

Head Height:

Between 0.312 inches and 0.327 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.623 inches and 0.624 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 6.240 inches and 6.260 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas6610 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.