

View Online at <https://aerobasegroup.com/nsn/5306-01-391-9678>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.438 inches

**Fastener Length:**

Between 2.985 inches and 3.015 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.156 inches and 0.171 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Grip Diameter:**

Between 0.311 inches and 0.312 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Single Shear Strength:**

95000 pounds per square inch

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 2.552 inches and 2.572 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.818 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 and steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6203 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.