

View Online at <https://aerobasegroup.com/nsn/5306-01-392-3404>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.670 inches

Fastener Length:

Between 2.551 inches and 2.571 inches

Head Style:

Hexagon

Head Height:

Between 0.251 inches and 0.266 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Grip Diameter:

Between 0.4986 inches and 0.4991 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.500 inches

Grip Length:

Between 1.875 inches and 1.891 inches

Thready Qty Per Inch (tpi):

20

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.415 inches first hole

Special Features:

Furnished with castellated nut retaining element; retaining element shall be released only by depressing plunger located in thread end of bolt

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0