## NSN 5306-01-392-3408

Shear Bolt - Page 1 of 2



AeroBase Group

**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 0.446 inches Fastener Length: Between 1.368 inches and 1.398 inches **Head Style:** Spline extended washer **Head Height:** Between 0.240 inches and 0.260 inches **Extended Washer Diameter:** Between 0.428 inches and 0.438 inches **Extended Washer Thickness:** Between 0.035 inches and 0.055 inches Hole Diameter: Between 0.032 inches and 0.042 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches Head Minor Diameter: 0.318 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.927 inches and 0.947 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch Hole Configuration Style: Double hexagon longitudinal hole Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response Surface Treatment: Passivate

## NSN 5306-01-392-3408

Shear Bolt - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0