

View Online at <https://aerobasegroup.com/nsn/5306-01-392-3415>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.530 inches

**Fastener Length:**

Between 2.131 inches and 2.151 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.157 inches and 0.172 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Grip Diameter:**

Between 0.3112 inches and 0.3117 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 1.625 inches and 1.641 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.015 inches first hole

**Special Features:**

Furnished with castellated nut retaining element; retaining element shall be released only by depressing plunger located in thread end of bolt

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0