## NSN 5306-01-392-3420



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-392-3420 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.446 inches **Fastener Length:** Between 0.743 inches and 0.773 inches **Head Style:** Spline extended washer **Head Height:** 0.250 inches **Extended Washer Diameter:** Between 0.428 inches and 0.438 inches **Extended Washer Thickness:** 0.045 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Head Minor Diameter:** Between 0.150 inches and 0.190 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unjf Shelf Life: N/a

## NSN 5306-01-392-3420

Shear Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0