## NSN 5306-01-392-5053

Shear Bolt - Page 1 of 2

**Thread Class:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-392-5053

Thread Direction:			
Right-hand			
Thread Length:			
0.390 inches			
Fastener Length:			
Between 0.755 inches and 0.775 inches			
Head Style:			
Double hexagon w/hole			
Head Height:			
Between 0.204 inches and 0.224 inches			
Width Between Flats:			
Between 0.243 inches and 0.251 inches			
Extended Washer Diameter:			
Between 0.359 inches and 0.369 inches			
Extended Washer Thickness:			
Between 0.040 inches and 0.060 inches			
Grip Diameter:			
Between 0.1885 inches and 0.1895 inches			
Single Shear Strength:			
132000 pounds per square inch			
Thread Diameter:			
0.190 inches			
Grip Length:			
0.375 inches			
Thready Qty Per Inch (tpi):			
32			
Min. Tensile Strength (psi):			
220000 pounds per square inch			
Surface Finish:			
32.0 microinches grip			
Material:			
Steel comp h11			
Material Specification:			
Ams 6487 assn standard single material response			
Surface Treatment:			
Nickel and cadmium and chromate			
Surface Treatment Specification:			
Ams 2416 assn standard all treatment responses			
Thread Series Designator:			
Unjf			

## NSN 5306-01-392-5053

Shear Bolt - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

80205-nas1785 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0