

View Online at <https://aerobasegroup.com/nsn/5306-01-392-5098>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.497 inches

**Fastener Length:**

Between 3.481 inches and 3.528 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.200 inches and 0.220 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.101 inches first hole and 0.111 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.3740 inches and 0.3745 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.316 inches first hole

**Product Name:**

Navy special project

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0