NSN 5306-01-392-5098



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-392-5098 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.497 inches **Fastener Length:** Between 3.481 inches and 3.528 inches **Head Style:** Double hexagon **Head Height:** Between 0.200 inches and 0.220 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Unthreaded Hole Diameter:** 0.101 inches first hole and 0.111 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.3740 inches and 0.3745 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 3.316 inches first hole **Product Name:** Navy special project Material: Nickel alloy 718 **Material Specification:** Ams5662 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-392-5098

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0