

View Online at <https://aerobasegroup.com/nsn/5306-01-393-1296>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

Between 3.693 inches and 3.713 inches

Head Style:

Dished hexagon

Head Height:

Between 0.126 inches and 0.141 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Grip Diameter:

Between 0.2487 inches and 0.2492 inches

Shank Unthreaded Hole Diameter:

0.076 inches threads and 0.086 inches threads

Thread Diameter:

0.250 inches

Grip Length:

Between 3.188 inches and 3.203 inches

Thready Qty Per Inch (tpi):

28

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.578 inches threads

Surface Finish:

32.0 microinches grip

Special Features:

Plunger protruding from head 0.076 in. Max

Material:

Stainless steel spring

Material Specification:

Qq-s-763 federal specification single material response locking feature

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0