

View Online at <https://aerobasegroup.com/nsn/5306-01-393-1297>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.375 inches

**Fastener Length:**

Between 1.115 inches and 1.135 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.126 inches and 0.141 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2487 inches and 0.2492 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches threads and 0.086 inches threads

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.625 inches and 0.641 inches

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.016 inches threads

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Plunger protruding from head 0.075 in. Max

**Material:**

Stainless steel spring or cobalt alloy spring

**Material Specification:**

Qq-s-763 assn standard single material response locking feature

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0