

View Online at <https://aerobasegroup.com/nsn/5306-01-394-0376>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.312 inches and 0.375 inches

**Fastener Length:**

1.062 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.260 inches

**Width Between Flats:**

0.250 inches

**Extended Washer Diameter:**

0.375 inches

**Extended Washer Thickness:**

0.040 inches

**First Diameter From Head:**

Between 0.146 inches and 0.150 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.812 inches and 0.816 inches

**End Application:**

F100 eng

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

130000 pounds per square inch

**Hardness Rating:**

24.0 rockwell c and 35.0 rockwell c

**Minimum Yield Strength:**

8500 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Altered item drawing make from ms9565-15

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0