

View Online at <https://aerobasegroup.com/nsn/5306-01-394-4491>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.593 inches

**Fastener Length:**

Between 4.053 inches and 4.083 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.280 inches and 0.300 inches

**Width Between Flats:**

Between 0.418 inches and 0.434 inches

**Extended Washer Diameter:**

Between 0.575 inches and 0.585 inches

**Extended Washer Thickness:**

0.021 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 3.465 inches and 4.485 inches

**Features Provided:**

Dry film lubricant

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Minimum Yield Strength:**

125000 pounds per square inch

**Color:**

Black threads

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Bms 10-85, type 1, cage 81205 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0