

View Online at <https://aerobasegroup.com/nsn/5306-01-394-6391>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.626 inches

Fastener Length:

Between 1.923 inches and 1.955 inches

Head Style:

Dished hexagon

Head Height:

Between 0.312 inches and 0.327 inches

Width Between Flats:

Between 0.926 inches and 0.940 inches

Grip Diameter:

Between 0.623 inches and 0.624 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Single Shear Strength:

95000 pounds per square inch

Thread Diameter:

0.625 inches

Grip Length:

Between 1.302 inches and 1.322 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.731 inches first hole

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6210 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.