

View Online at <https://aerobasegroup.com/nsn/5306-01-394-7862>

Thread Class:

Aal

Thread Direction:

Right-hand

Thread Length:

Between 1.013 inches and 1.017 inches

Fastener Length:

Between 5.075 inches and 5.095 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.376 inches and 0.381 inches

Width Between Flats:

Between 1.052 inches and 1.064 inches

Locking Feature:

Retainer fastener

Grip Diameter:

Between 0.748 inches and 0.749 inches

Shank Unthreaded Hole Diameter:

0.067 inches first hole and 0.087 inches first hole

Thread Diameter:

0.750 inches

Grip Length:

Between 4.062 inches and 4.078 inches

Features Provided:

Cotter pin

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

95000 pounds per square inch

Hardness Rating:

36.0 rockwell c fastener and 41.0 rockwell c fastener

Surface Finish:

63.0 microinches grip

Material:

Steel comp e4340 and steel comp 4140 and steel comp 8740 and steel comp 4130 and steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0