

View Online at <https://aerobasegroup.com/nsn/5306-01-394-7865>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.012 inches and 1.016 inches

Fastener Length:

Between 5.387 inches and 5.407 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.501 inches and 0.516 inches

Width Between Flats:

Between 1.427 inches and 1.440 inches

Locking Feature:

Retainer fastener

Grip Diameter:

Between 0.9972 inches and 0.9991 inches

Shank Unthreaded Hole Diameter:

0.067 inches first hole and 0.087 inches first hole

Thread Diameter:

1.000 inches

Grip Length:

Between 4.375 inches and 4.391 inches

Features Provided:

Cotter pin

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

95000 pounds per square inch

Hardness Rating:

36.0 rockwell c fastener and 41.0 rockwell c fastener

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.240 inches first hole and 5.250 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 4130 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0