NSN 5306-01-395-1233

Shear Bolt - Page 1 of 2



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** 1.293 inches Fastener Length: Between 4.481 inches and 4.511 inches **Head Style:** Spline extended washer **Head Height:** Between 0.590 inches and 0.610 inches **Extended Washer Diameter:** Between 1.384 inches and 1.394 inches **Extended Washer Thickness:** Between 0.098 inches and 0.118 inches **Grip Diameter:** Between 0.7480 inches and 0.7490 inches Head Minor Diameter: Between 0.797 inches and 0.812 inches **End Application:** Pacer dawn **Thread Diameter:** 0.750 inches Grip Length: Between 3.178 inches and 3.198 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 103000 pounds per square inch Cadmium **Surface Treatment Specification:**

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Mil-c-8837, type ii, class 2 military specification single treatment response

Thread Series Designator:

Unjf



NSN 5306-01-395-1233

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

