

View Online at <https://aerobasegroup.com/nsn/5306-01-395-1236>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.293 inches

**Fastener Length:**

Between 4.731 inches and 4.761 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.590 inches and 0.610 inches

**Extended Washer Diameter:**

Between 1.384 inches and 1.394 inches

**Extended Washer Thickness:**

Between 0.098 inches and 0.118 inches

**Grip Diameter:**

Between 0.7480 inches and 0.7490 inches

**Head Minor Diameter:**

Between 0.797 inches and 0.812 inches

**End Application:**

Pacer dawn

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 3.428 inches and 3.448 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

103000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c and 54.0 rockwell c

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837, type ii, class2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.