NSN 5306-01-395-2162

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-395-2162

3a
Thread Direction:
Right-hand
Thread Length:
0.903 inches
Fastener Length:
Between 3.638 inches and 3.668 inches
Head Style:
Spline extended washer
Head Height:
Between 0.440 inches and 0.460 inches
Extended Washer Diameter:
Between 0.818 inches and 0.828 inches
Extended Washer Thickness:
Between 0.092 inches and 0.112 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Head Minor Diameter:
Between 0.644 inches and 0.651 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 2.740 inches and 2.760 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches head
Color:
White head
Material:
Steel comp 8740 or steel comp e4340
Material Specification:
Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response
Surface Treatment:
Cadmium and chromate

NSN 5306-01-395-2162

Shear Bolt - Page 2 of 2



Surface Treatment Specification:
Qq-p-416, ty2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

A003b0

Fiig:

Mil-std (military Standard):

Mil-s-6049 spec.