

View Online at <https://aerobasegroup.com/nsn/5306-01-395-3584>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.730 inches and 0.740 inches

Fastener Length:

Between 4.345 inches and 4.375 inches

Head Style:

Dished hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Hole Diameter:

Between 0.070 inches and 0.080 inches

Grip Diameter:

Between 0.4990 inches and 0.4995 inches

Single Shear Strength:

95000 pounds per square inch

Thread Diameter:

0.500 inches

Grip Length:

Between 3.615 inches and 3.635 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Hexagon corners

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6708 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0