## NSN 5306-01-395-3584

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-395-3584

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.730 inches and 0.740 inches
Fastener Length:
Between 4.345 inches and 4.375 inches
Head Style:
Dished hexagon
Head Height:
Between 0.250 inches and 0.265 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.4990 inches and 0.4995 inches
Single Shear Strength:
95000 pounds per square inch
Thread Diameter:
0.500 inches
Grip Length:
Between 3.615 inches and 3.635 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## NSN 5306-01-395-3584

Shear Bolt - Page 2 of 2

A003b0



Thread Series Designator:
Unjf
Specification Data:
80205-nas6708 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: