

View Online at <https://aerobasegroup.com/nsn/5306-01-398-1262>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.095 inches and 1.155 inches

Shank Length:

Between 1.095 inches and 1.155 inches

Eye Stock Diameter:

1.375 inches

Shoulder Diameter:

Between 0.993 inches and 0.998 inches

Shoulder Length:

5.375 inches

Ring Stock Diameter:

0.687 inches

Ring Inside Diameter:

Between 2.380 inches and 2.620 inches

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Special Features:

Threads undercut for relief, 0.125 in. Max. Undercut length

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response

Surface Treatment:

Cadmium and chromate or zinc and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification 1st treatment response or qq-z-325 type 2 cl 3 federal specification 2nd treatment response

Style Designator:

Swivel

Thread Series Designator:

Unjf

Specification Data:

80205-nas1251 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.