NSN 5306-01-398-5272

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-398-5272 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.470 inches and 0.500 inches **Fastener Length:** Between 1.330 inches and 1.370 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.563 inches **Head Height:** Between 0.368 inches and 0.375 inches **First Diameter From Head:** 0.312 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.850 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.3125 inches and 0.3160 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Material Specification:** Astm a493 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 1, 2, or 3 federal specification single treatment response

Unf

Shelf Life:

Thread Series Designator:

N/a

NSN 5306-01-398-5272

Internal Wrenching Bolt - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A003b0