

View Online at <https://aerobasegroup.com/nsn/5306-01-398-9467>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.568 inches and 0.573 inches

**Fastener Length:**

Between 1.375 inches and 1.390 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.678 inches and 0.690 inches

**Grip Diameter:**

Between 0.4365 inches and 0.4370 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.802 inches and 0.822 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.183 inches first hole and 1.188 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Titanium alloy uns r56400

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6806 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0