NSN 5306-01-399-6110



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-399-6110 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** Between 0.704 inches and 0.734 inches **Head Style:** Hexagon extended washer **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Extended Washer Diameter:** 0.460 inches **Extended Washer Thickness:** Between 0.240 inches and 0.260 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.3125 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:**

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5306-01-399-6110

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.