NSN 5306-01-400-1003

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-400-1003

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.902 inches
Fastener Length:
Between 3.387 inches and 3.417 inches
Head Style:
Dished hexagon
Head Height:
Between 0.312 inches and 0.327 inches
Width Between Flats:
Between 0.928 inches and 0.940 inches
Grip Diameter:
Between 0.6230 inches and 0.6240 inches
Thread Diameter:
0.625 inches
Grip Length:
Between 2.490 inches and 2.510 inches Features Provided:
Finished head Thready Oty Par Inch (tri)
Thready Qty Per Inch (tpi):
18 Min Tanaila Strangth (nai)
Min. Tensile Strength (psi):
160000 pounds per square inch Minimum Yield Strength:
95000 pounds per square inch
Surface Finish:
32.0 microinches threads
Color:
Green threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unif

NSN 5306-01-400-1003

Shear Bolt - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

80205-nas6710 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0