

View Online at <https://aerobasegroup.com/nsn/5306-01-400-1782>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.694 inches

Fastener Length:

Between 2.554 inches and 2.584 inches

Head Style:

Dished hexagon

Head Height:

Between 0.219 inches and 0.234 inches

Width Between Flats:

Between 0.678 inches and 0.690 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.4375 inches

Grip Length:

Between 1.865 inches and 1.885 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.587 inches first hole

Material:

Steel comp 4340 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas6607 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0