NSN 5306-01-400-3238

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-400-3238

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
Between 0.892 inches and 0.922 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.428 inches and 0.448 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Minimum Yield Strength:
95000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6805 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-01-400-3238

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0