NSN 5306-01-400-3473

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-400-3473 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.733 inches **Fastener Length:** Between 3.968 inches and 3.998 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.485 inches and 0.500 inches **Extended Washer Diameter:** Between 0.740 inches and 0.750 inches **Extended Washer Thickness:** Between 0.089 inches and 0.109 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **End Application:** B52h **Thread Diameter:** 0.4375 inches **Grip Length:** Between 3.150 inches and 3.350 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-400-3473

Shear Bolt - Page 2 of 2



	• •			
 n	1+	<i>(</i>)+	Meas	uro.

--

Demilitarization:

No

Fiig:

A003b0