NSN 5306-01-406-5010

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-406-5010 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.454 inches **Fastener Length:** Between 1.564 inches and 1.594 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Grip Diameter:** Between 0.4047 inches and 0.4057 inches **Thread Diameter:** 0.3750 inches **Grip Length:** Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization:

NSN 5306-01-406-5010

Shear Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.