## NSN 5306-01-406-5445

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-406-5445

Thursday	01
Thread	Class:

A3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

0.370 inches

#### Fastener Length:

Between 3.4175 inches and 3.4475 inches

#### Head Style:

Dished hexagon

#### Head Height:

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.429 inches and 0.439 inches

#### Grip Diameter:

Between 0.2485 inches and 0.2495 inches

**Thread Diameter:** 

0.2500 inches

#### Grip Length:

Between 3.0525 inches and 3.0725 inches

#### Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp e4340 or steel comp 8740

#### **Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard

2nd material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

#### Thread Series Designator:

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

### Fiig:

A003b0

# NSN 5306-01-406-5445

Shear Bolt - Page 2 of 2

### Mil-std (military Standard):

Mil-s-5000 spec.

