## NSN 5306-01-407-7184

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-407-7184

| Thread | Class: |
|--------|--------|

3a

**Thread Direction:** 

Right-hand

## Thread Length:

0.578 inches

### Fastener Length:

Between 2.438 inches and 2.468 inches

#### **Head Style:**

Dished hexagon

#### Head Height:

Between 0.188 inches and 0.203 inches

## Width Between Flats:

Between 0.554 inches and 0.564 inches

#### Grip Diameter:

Between 0.3735 inches and 0.3745 inches

#### **Thread Diameter:**

0.375 inches

## Grip Length:

Between 1.865 inches and 1.885 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

## Material:

Steel comp e4340 or steel comp 8740

## Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard

3rd material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

## **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas6606 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

# NSN 5306-01-407-7184

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

