NSN 5306-01-407-9482

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-407-9482

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.735 inches |
| Fastener Length: |
| Between 1.782 inches and 1.812 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.250 inches and 0.265 inches |
| Width Between Flats: |
| Between 0.741 inches and 0.752 inches |
| Hole Diameter: |
| Between 0.070 inches and 0.080 inches |
| Grip Diameter: |
| Between 0.4990 inches and 0.4995 inches |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| Between 1.052 inches and 1.072 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| |

NSN 5306-01-407-9482

Close Tolerance Bolt - Page 2 of 2



Specification Data:

80205-nas6708 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0