

View Online at <https://aerobasegroup.com/nsn/5306-01-412-1736>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.902 inches

Fastener Length:

Between 1.137 inches and 1.177 inches

Head Style:

Dished hexagon

Head Height:

Between 0.375 inches and 0.390 inches

Width Between Flats:

Between 1.052 inches and 1.064 inches

Shoulder Diameter:

0.7480 inches first shoulder and 0.7490 inches first shoulder

Shoulder Length:

0.240 inches first shoulder and 0.260 inches first shoulder

Shank Unthreaded Hole Diameter:

0.141 inches threads and 0.151 inches threads

Thread Diameter:

0.625 inches

Thready Qty Per Inch (tpi):

18

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.903 inches threads

Shoulder Shape:

Round first shoulder

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0