

View Online at <https://aerobasegroup.com/nsn/5306-01-412-4848>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.454 inches

Fastener Length:

0.829 inches

Head Style:

Hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.3729 inches and 0.3735 inches

Hole Diameter:

Between 0.070 inches and 0.080 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 0.365 inches and 0.385 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Hole Configuration Style:

Hexagon flats

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.646 inches first hole

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas6206 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0