NSN 5306-01-412-4891

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-412-4891

reace Classe: Sa Thread Classe: Righ-hand Thread Length: 0537 Inches 6538 Inches Fastear Length: 0538 Inches Fastear Length: 0548 Inches 68 Vectoriolis Fastear Douting: 0542 Inches Fastear Douting: 1054 Diameter: 1054 Diameter: 1054 Diameter: 1053 Diametes 1054 Diameter: 1053 Diametes 1054 Diameter: 1053 Diametes 1054 Diameter: 1053 Diametes 1054 Diameter: 1054 Diameter: 1054 Diameter: 1054 Diameter: 1054 Diameter:	
Firsterion: Riscelangi: 0.537 indes 0.538 indus Pateore 0.688 indus Pateore 0.680 indus 0.690 indus 0.700 indus 0.700 indus 0.710 indus 0.720 indus </td <td>Thread Class:</td>	Thread Class:
Pighthand Pighthand <td< td=""><td>За</td></td<>	За
Fract Lengt:0.537 indesFastner Lengt:6.688 indesHead Style:6.888 indesHead Style:8-wet-onicalHead Style:8-wet-onicalHead Diameter:Betwet-0.621 inches and 0.531 inchesHead Taineter:0.312 inchesHold Diameter:0.323 inches and 0.060 inchesHold Diameter:1000000000000000000000000000000000000	Thread Direction:
9.837 inches9.838 inches9.848 inches9.848 inches9.848 inches9.848 inches9.849 inches9.849 inches and 0.531 inches9.849 inches and 0.531 inches9.841 inches and 0.531 inches9.842 inches <td< td=""><td>Right-hand</td></td<>	Right-hand
Faster Length: 588 inclos 588 inclos Seave-Concil Bowe-Concil Bowe-Docal Head Diameter: Concil Concil Concil Bowe-Docal incloses and 0.531 inclose Head Height: Concil	Thread Length:
588 Inches Beds Syle: Beds Concild Head Syle: Beds Concild Head Dimmeter: Between 0521 inches and 0.531 inches Head Height: 0.312 inches Head Dimmeter: Between 0.656 inches and 0.060 inches Internal Drive Style: Asagon Thread Diameter: 0.312 inches O.312 inches With Across Flats: Stewen 0.219 inches and 0.221 inches Hele Quantity: 4 Hole Steps: Dirikd Thread Dirike Steps: Proceed Quantity: 4 Hole Steps: Dirikd Thread Chap: Paradox Quart Inch (ps): Rowen 0.219 inch (ps): 10000 pounds per square inch Hacross Reting: 10100 pounds per square inch Hacross Reting: 10200 pounds per square inch Hacross Reting: 10200 pounds per square inch Hacross Reting: 10200 pounds per square inch Hacro	0.537 inches
Had Style: Revel-conical Revel-conical Had Nameer: Retwen 0.521 inches and 0.531 inches Had Holp: 0.312 inches Had Kolp: 0.312 inches Had Nameer: Reven 0.055 inches and 0.060 inches Hernal Drive Style: Reven 0.055 inches and 0.060 inches Hardan Drive Style: Reven 0.051 inches and 0.201 inches Match Stress Betwen 0.219 inches and 0.221 inches Hold Constret: Paradox Paradox Hold Constret:	Fastener Length:
Personal Personal <t< td=""><td>5.688 inches</td></t<>	5.688 inches
Had Diameter: Exteuen 0.521 Inches and 0.531 Inches Height: 0.312 Inches 0.312 Inches Betwen 0.055 Inches and 0.060 Inches Heidmann: Exteuen 0.055 Inches and 0.060 Inches Intrad Diameter: 0.312 Inches Victor State: 0.312 Inches Victor Cores Flats: 0.420 Control: 0.421 Inches and 0.221 Inches and 0.221 Inches Pole Quantity: 4 Pole Yoe: 1010000000000000000000000000000000000	Head Style:
Between 0.521 inches and 0.531 inches Head Height: 0.312 Inches Hole Diameter: Botween 0.505 inches and 0.060 inches Herral Drive Skyle: Precad Diameter: 0.312 Inches Witch Accoss Flats: Botween 0.221 Inches and 0.221 inches Hole Quantity: 4 Hole Strippe: Dilded Dilded Dilded Horshyle: Autorson Flats: Botween 0.219 Inches and 0.221 inches Hole Quantity: 4 Hole Strippe: Dilded Thready Gty Per Inch (pt): 24 Horson String: 100000 pounds per square inch Hardess Rating: 34.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Rotan internal hexagon Hardess Rating: Stel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Hole-Stope flatation 1st material response or mil-s-6038 military specification 2nd material response or mil-s-6048 military specification 2nd material response or mil-s-6049 military specification 5th material response or mil-s-6	Bevel-conical
Head Height: 0.312 inches 0.312 inches Head Dameter: Istema Dröve Style: Hexago Thread Diameter: 0.312 inches 0.312 inches Viet Across Flats: Betwen 0.021 9 inches and 0.221 inches Hole Quantity: 4 Hole Yope: Jille Priedbard Hole Strength (psi): A Hole Strength (psi): 10000 pounds per square inch Hordense Rating: 10000 pounds per square inch 10000 pounds p	Head Diameter:
0.312 indes Hol Dameer: 0.6 keen 0.055 inches and 0.060 inches Hervag 0 Horvag 1 Hervag 1 Horvag 1 H	Between 0.521 inches and 0.531 inches
Hole Diameter: Between 0.055 inches and 0.060 inches Hernal Drive Style: Hernal Drive Style: Harsagn Tracea Diameter: 0.312 inches Bitter Statis: Between 0.219 inches and 0.221 inches Hole Quantity: Participation Statis: Botter Drive: Participation Statis: Protect Statis:<	Head Height:
Between 0.055 inches and 0.060 inches Interal Drive Style: Hexagon Tread Diameter: 0.312 inches With Across Flats: Between 0.219 inches and 0.221 inches Hole Quantity: 4 Hole Type: Drilled Thready Gty Per Inch (tpi): 24 Hone Strangth (psi): 10000 pounds per square inch Hone Strangth (psi): 10000 pounds per square inch Hordenstrangth (psi): 10100 pounds per square inch Bound internal hexagon Hordenstrangth (psi): 1010 pounds per square inch	0.312 inches
Ineral Drive Style: Hexagon Tread Diameter: 0.312 Inches With Across Flats: Determine Style: Betwen 0.219 Inches and 0.221 Inches Hole Quantity: 4 Hole Type: Drilled Tready Oty Per Inch (tpi): 24 Mino Type Inch (tpi): 24 Mologo pounds per square Inch Minoto Style: 3000 pounds per square Inch Horders Rating: 304 Octowell c Horders Rating: 304 Octowell c Horders Rating: 304 Octowell c Material Bectorne per 430 or steel comp 4740 or steel comp 8740 or steel comp 6150 Mile-Stolon military specification 1st material response or mil-s-6626 military specification 2nd material response or mil-s-6698 military specification 2nd material response or mile-s6698 military specification 2nd material response or mile-s6686 military specification 2nd material response or mile-s6698 m	Hole Diameter:
Hexagon Thread Diameter: 0.312 Inches Width Across Flats: Between 0.219 Inches and 0.221 Inches Hole Quantity: 4 Hole Street Joild Forser Drilled Thready Oxy Oxy For Inch (tpi): 24 Honderstreet Min. Tensile Strength (psi): 10000 pounds per square inch Hordenstreet 4000 concluse per square inch Hordenstreet 10000 pounds per square inch 10000 p	Between 0.055 inches and 0.060 inches
Incead Diameter: 0.312 inches Vidth Across Flats: Between 0.219 inches and 0.221 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Honesse Rating: 160000 pounds per square inch Hardness Rating: 170000 conclusters of the dual of t	Internal Drive Style:
0.312 Inches With Across Flats: Between 0.219 Inches and 0.221 inches Hole Quantity: 4 Hole Type: Dilled Fready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 10000 pounds per square inch Min. Strength (psi): 104.000 rockwell c Min. Tensile Strength (psi): 105.000 pounds per square inch Hole Configuration Style: 106.000 rockwell c Hole Configuration Style: 108.000 pounds or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Mirei Stoon military specification 1st material response or mil-s-6028 military specification 2nd material response or mil-s-6049 military specification 5nd material response or mil-s-6049 military specification 2nd material response or mil-s-6049 military specification 2nd material response or mil-s-6049 military specification 5nd material response or mil-s-6049 military specification 2nd material response or mil-s-6049 military specific	Hexagon
With Across Flats:Between 0.219 inches and 0.221 inchesHole Quantity:4Hole Type:DrilledDrilledThready Cty Per Inch (tpi):24Boot Spreigneigneigneigneigneigneigneigneigneign	Thread Diameter:
Between 0.219 inches and 0.221 inches Hole Quantity: 4 Hole Type: Drilled Tready Oty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hordense Rating: 34.0 rockwell c and 40.0 rockwell c Hordense Rating: Storo on internal hexagon Material: Steel comp e4340 or steel comp 4740 or steel comp 8735 or steel comp 6150 Miles-5000 military specification 1st material response or mil-s-6028 military specification 2nd material response or mil-s-6049 military specification 3rd material response or miles-6098 military specification 4th material response or miles-6049 military response Surface Treatment: Cadmium and chromate	0.312 inches
Hole Quantity: 4 Hole Type: Drilled Tready Qty Per Inch (tpi): 24 Monor Series Strength (psi): 160000 pounds per square inch 160000 pounds per square inch 16100000000000000000000000000000000000	Width Across Flats:
4 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 16000 pounds per square inch Hardness Rating: 34. or ockwell c Hole Configuration Style: Roud internal hexagon Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military response Strafeer Treatment: Cadmium and chromate	Between 0.219 inches and 0.221 inches
Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 34.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Round internal hexagon Material Sterial Specification Mils-s6000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military response Sufface Treatment: Cadmium and chromate	Hole Quantity:
Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 34.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Round internal hexagon Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military response Surface Treatment: Cadmium and chromate	4
 Frready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 34.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Round internal hexagon Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification Mil-s-5000 military specification 1st material response or mil-s-6098 military specification 2nd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material Forface Treatment: Cadmium and chromate 	Hole Type:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 34.0 rockwell c and 40.0 rockwell c Hoconfiguration Style: Round internal hexagon Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-s-5000 military specification 1st material response or mil-s-6262 military specification 2nd material response or mil-s-6049 military response Strafee Treatment: Cadmium and chromate	Drilled
 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 34.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Round internal hexagon Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-s-5000 military specification 1st material response or mil-s-6098 military specification 2nd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material Forface Treatment: Cadmium and chromate 	Thready Qty Per Inch (tpi):
 160000 pounds per square inch Hardness Rating: 34.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Round internal hexagon Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-s-5000 military specification 1st material response or mil-s-6266 military specification 2nd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military For Freatment: Cadmium and chromate 	24
 Hardness Rating: 34.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Round internal hexagon Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-s-5000 military specification 1st material response or mil-s-6266 military specification 2nd material response or mil-s-6098 military specification 2nd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response Surface Treatment: Cadmium and chromate 	Min. Tensile Strength (psi):
 34.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Round internal hexagon Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response Surface Treatment: Cadmium and chromate 	160000 pounds per square inch
Hole Configuration Style:Round internal hexagonMaterial:Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150Material Specification:Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 militarypecification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th materialresponseSurface Treatment:Cadmium and chromate	Hardness Rating:
Round internal hexagonMaterial:Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150Material Specification:Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 militaryspecification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th materialresponseSurface Treatment:Cadmium and chromate	34.0 rockwell c and 40.0 rockwell c
Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response Surface Treatment: Cadmium and chromate	Hole Configuration Style:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response Surface Treatment: Cadmium and chromate	Round internal hexagon
Material Specification: Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response Surface Treatment: Cadmium and chromate	Material:
Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response Surface Treatment: Cadmium and chromate	Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response Surface Treatment: Cadmium and chromate	Material Specification:
response Surface Treatment: Cadmium and chromate	Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military
Surface Treatment: Cadmium and chromate	specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material
Cadmium and chromate	response
	Surface Treatment:
Surface Treatment Specification:	Cadmium and chromate
	Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

NSN 5306-01-412-4891

Internal Wrenching Bolt - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.