

View Online at <https://aerobasegroup.com/nsn/5306-01-412-6056>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.627 inches

Fastener Length:

Between 8.173 inches and 8.203 inches

Head Style:

Hexagon

Head Height:

Between 0.375 inches and 0.390 inches

Width Between Flats:

Between 1.062 inches and 1.064 inches

Grip Diameter:

Between 0.748 inches and 0.749 inches

Shank Unthreaded Hole Diameter:

0.141 inches threads and 0.151 inches threads

Thread Diameter:

0.750 inches

Grip Length:

Between 1.178 inches and 1.198 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

8.549 inches threads and 8.577 inches threads

Material:

Steel

Material Specification:

Mil-b-7838 military specification all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-b-7838 spec.