

View Online at <https://aerobasegroup.com/nsn/5306-01-413-3752>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.763 inches

**Fastener Length:**

Between 2.638 inches and 2.668 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.383 inches and 0.403 inches

**Width Between Flats:**

Between 0.485 inches and 0.500 inches

**Extended Washer Diameter:**

Between 0.807 inches and 0.817 inches

**Extended Washer Thickness:**

Between 0.063 inches and 0.073 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**End Application:**

Pacer dawn

**Thread Diameter:**

0.4375 inches

**Grip Length:**

Between 1.865 inches and 1.885 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837, type ii, class 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.