

View Online at <https://aerobasegroup.com/nsn/5306-01-413-3752>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.763 inches

Fastener Length:

Between 2.638 inches and 2.668 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.383 inches and 0.403 inches

Width Between Flats:

Between 0.485 inches and 0.500 inches

Extended Washer Diameter:

Between 0.807 inches and 0.817 inches

Extended Washer Thickness:

Between 0.063 inches and 0.073 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

End Application:

Pacer dawn

Thread Diameter:

0.4375 inches

Grip Length:

Between 1.865 inches and 1.885 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type ii, class 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.