NSN 5306-01-413-5254

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-413-5254 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.620 inches and 0.640 inches **Fastener Length:** Between 0.990 inches and 1.010 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** 0.040 inches **First Diameter From Head:** Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.248 inches **End Application:** Pacer dawn **Thread Diameter:** 0.1900 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 36.0 rockwell c and 45.0 rockwell c **Externally Relieved Body Diameter Quantity: Special Features:** Original name-bolt, machine-double Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-413-5254

Externally Relieved Body Bolt - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A003b0