## NSN 5306-01-413-5447

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-413-5447

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.733 inches  |
| Fastener Length:  |
| Between 2.468 inches and 2.498 inches                         |
| Head Style:   |
| Double hexagon extended washer                                |
| Head Height:  |
| Between 0.365 inches and 0.385 inches                         |
| Width Between Flats:  |
| Between 0.561 inches and 0.580 inches                         |
| Extended Washer Diameter:                                     |
| Between 0.740 inches and 0.750 inches                         |
| Extended Washer Thickness:                                    |
| Between 0.089 inches and 0.109 inches                         |
| Grip Diameter:  |
| 0.4512 inches   |
| Thread Diameter:  |
| 0.4375 inches   |
| Grip Length:  |
| Between 1.740 inches and 1.760 inches                         |
| Thready Qty Per Inch (tpi):                                   |
| 20  |
| Min. Tensile Strength (psi):                                  |
| 200000 pounds per square inch                                 |
| Special Features:   |
| Oversize  |
| Material:   |
| Iron alloy 660  |
| Material Specification:                                       |
| Ams 5737 assn standard single material response               |
| Surface Treatment:  |
| Aluminum  |
| Surface Treatment Specification:                              |
| Bms10-85 type 1 cagec 81205 mfr ref single treatment response |
| Thread Series Designator:                                     |
| Unjf  |
| Shelf Life:   |
| N/a   |
|   |

## NSN 5306-01-413-5447

Close Tolerance Bolt - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

