NSN 5306-01-413-8219

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-413-8219

| Thread Class: |
|--------------------------------------------------------------------------------------------------|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.298 inches and 0.348 inches |
| Fastener Length: |
| Between 1.746 inches and 1.776 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.110 inches and 0.125 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| End Application: |
| Pacer dawn |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 1.428 inches and 1.448 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5731 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, ty2, cl2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5306-01-413-8219

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0